

EMERGENCY CONTACTS

Emergency Contact Number: 0417 658 121 (Normal Business Hours & After Hours)
Sydney Poisons Information Centre: 131 126

IDENTIFICATION

NOT CLASSED AS HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA

Product Name:	Formula 207	UN Number:	1300
Other Name:		Dangerous Goods Class:	3
Manufacturers Code:		Subsidiary Risk:	3
Use:	Solvent	Hazchem Code:	3 (Y)
Poisons Schedule:	S5		

PHYSICAL DESCRIPTION / PROPERTIES

Appearance & Odour:	Green Liquid	Boiling Point:	>149 deg C
Specific Gravity:	0.86	Solubility in Water:	Not soluble in water
Flash point:	Approx 36C (flammable)	Melting Point:	Approx – 54C
Vapour Pressure:	<25.0 mm Hg at 25C	Flammability Limit:	LEL 0.8% UEL 6.0%

OTHER PROPERTIES

pH: Not Applicable

CHEMICAL INGREDIENTS

Chemical Entity	Cas Number	Proportion
Light aromatic petroleum solvent	64742-95-6	Less than 60%
Medium aliphatic petroleum solvent	64742-88-7	Less than 60%
Nonyl Phenol Ethoxylate	26027-38-3	Less than 10%

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Swallowed:	Practically non-toxic (LD 50: >2000mg/kg)
Eye:	Practically non-irritating (Draize Score: >6 but <15 or less)
Skin:	Practically non-toxic (LD 50: >2000mg/kg)
Inhaled:	Practically non-toxic

FIRST AID

Swallowed:	DO NOT INDUCE VOMITING. Give water or milk to drink. Seek medical assistance
Eye:	Irrigate with copious quantity of water for at least 15 minutes. If irritation persists, call a doctor.
Skin:	Wash contact areas with water. Remove contaminated clothing. Launder contaminated clothing before re-use
Inhaled:	Remove from further exposure. If respiratory irritation, dizziness, nausea or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, use mouth to mouth resuscitation.
First Aid Facilities:	No special facilities required
Advice to Doctor:	Treat symptomatically. Material if aspirated into the lungs may cause chemical pneumonitis.

PRECAUTIONS FOR USE

Exposure Standards:	100 ppm
Flammability:	Flammable
Ventilation:	Use in a well ventilated area. Use away from all ignition sources

PERSONAL PROTECTION

Eye Protection:	Normal industrial eye protection practices should be employed.
Skin:	If prolonged or repeated skin contact is likely to occur, oil impervious gloves should be worn. Good personal hygiene practices should always be followed.

FLAMMABILITY

Fire/Explosion Hazard:	Flammable. Use water to cool fire-exposed containers. If leak has not ignited, protect personnel by dispersing the vapours with water spray. Prevent run-off from fire control of dilution from entering waterways, sewers or drinking water supply.
-------------------------------	--

SAFE HANDLING INFORMATION

Storage and Transport:	Storage containers should be grounded and banded, with self-closing valves, pressure vacuum bungs and flame arresters. Store in a cool area away from all ignition sources. Avoid sparking conditions.
Spills and Disposal:	Contain and absorb on fire retardant treated sawdust, diatomaceous earth, etc. Shovel up and dispose at an appropriate licensed waste disposal site in accordance with current applicable laws and regulations. Remove leaking containers to detached area. Product may be disposed by supervised incineration.

OTHER INFORMATION

Stability:	Stable
Conditions to Avoid:	Heat, sparks, flame and build up of static electricity
Incompatibility:	Strong oxidizers
Decomposition Produce:	Carbon mono and multi oxides

While the information contained herein is correct to the best of our knowledge. Osher Chemicals herein disclaims any warranties as to the accuracy of the same. Recommendations or suggestions are made without guarantee or representation as to the result, since conditions of use are beyond our control. All materials are sold subject to and on conditions that the buyer shall make his own test to determine the suitability of such product for buyer's purposes. No statement contained herein shall be constructed as a recommendation to infringe any patent.

Dated – April, 2006