



11/10 Prosperity Parade, Warriewood, NSW 2102
 PO Box 5099, Elanora Heights, NSW 2101
 Ph: 9997 6900 Fax: 9997 6999
 sales@osher.com.au www.osher.com.au

EMERGENCY CONTACTS

Emergency Contact Number: 0417 658 121 (Normal Business Hours & After Hours)
 Sydney Poisons Information Centre: 131 126

IDENTIFICATION

CLASSED AS HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA

Product Name:	Paint Stripper	UN Number:	2810
Other Name:		Dangerous Goods Class:	6.1
Manufacturers Code:		Subsidiary Risk:	None
Use:	Paint stripper	Hazchem Code:	2X
Poisons Schedule:	S5		

PHYSICAL DESCRIPTION / PROPERTIES

Appearance & Odour:	Liquid	Boiling Point:	
Specific Gravity:		Solubility in Water:	Mixes with water
Vapour Pressure:		Melting Point:	
Flammability Limits:			

OTHER PROPERTIES

CHEMICAL INGREDIENTS

Chemical Entity	Cas Number	Proportion (%)	TWA
Methylene chloride	75-09-2	>60	50 ppm
Performance additives		10-30	

PRODUCT: Paint Stripper

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Swallowed:	Harmful. Irritating to respiratory system
Eye:	Irritating to eyes
Skin:	Irritating to skin. Can be absorbed through skin. Harmful in contact with skin.
Inhaled:	Harmful by inhalation. Vapours may cause dizziness or suffocation.
Chronic:	Possible risk of irreversible effects. Danger of cumulative affects.

FIRST AID

Swallowed:	Do not induce vomiting. Give milk or water. Seek medical advice
Eye:	Wash with running water (15 mins.) Seek medical attention.
Skin:	Remove contaminated clothing. Wash with water and soap.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Seek medical attention.
Advice to Doctor:	Treat symptomatically. No adrenaline. Evaluate for respiratory distress. Decontaminate. NO adrenaline. Monitor carboxyhaemoglobin.

PRECAUTIONS FOR USE

Engineering Controls:	General exhaust ventilation adequate
Glasses:	Safety glasses. Chemical goggles.
Gloves:	1. PE/EVAL/PE 2. PVA 3. TEFLON
Respirator:	Type AX Filter of sufficient capacity

SAFE HANDLING INFORMATION

Storage and Transport:	Keep container tightly closed. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Store in a cool, dry, protected area.
Spills and Disposal:	Spilled liquid has low temperature and evaporates quickly. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/fog. Absorb with dry agent. Stop leak if safe to do so. Take off immediately all contaminated clothing. To clean the floor and all objects contaminated by this material, use water.
Fire and Explosions:	Vapours/gas heavier than air. Toxic smoke/fumes in a fire
Fire fighting:	Water spray/fog

OTHER INFORMATION

While the information contained herein is correct to the best of our knowledge. OSHER Chemicals herein disclaims any warranties as to the accuracy of the same. Recommendations or suggestions are made without guarantee or representation as to the result, since conditions of use are beyond our control. All materials are sold subject to and on conditions that the buyer shall make his own test to determine the suitability of such product for buyer's purposes. No statement contained herein shall be constructed as a recommendation to infringe any patent.

Dated – April 2007